

## **KEEPING YOU IN CHARGE**









# PSC-122000ACX 12V 2A

**Sealed Lead Acid Battery Charger ACX Battery Charger Series** 

## **FEATURES**

- Universal input voltage range 90VAC 240VAC
- Automatic, current sensing dual-rate charging for efficient, care-free and safe operation
- LED indicators
- Universal leads & plugs


## **APPROVALS**

- Approved for transport by air. D.O.T., I.A.T.A., F.A.A. and C.A.B. certified
- DOE

ETL

- ISO9001:2015 Quality management systems
- FCC
- CE

### **CHARGER CHARACTERISTICS**



#### **GLOBAL HEADOUARTERS**

(USA AND INTERNATIONAL EXCLUDING EMEA)

**Power-Sonic Corporation** 365 Cabela Dr Suite 300, Reno, Nevada 89439 USA

T: +1 775 824 6500

E: customer-service@power-sonic.com

#### **POWER-SONIC EMEA**

(EMEA - EUROPE, MIDDLE EAST AND AFRICA)

Smitspol 4, 3861 RS Nijkerk, The Netherlands

T NL: + 31 33 7410 700 TUK: +44 1268 560 686 TFR: +33 344 32 18 17

E: salesEMEA@power-sonic.com

#### PERFORMANCE SPECIFICATIONS

#### Input Specs

AC input voltage rating 100Vac-240Vac 50Hz-60Hz AC input frequency rating AC input voltage range 90Vac-240Vac AC input frequency range 47Hz-63Hz

AC input current 3.0A@115Vac/1.8A@230Vac

40W AC input power 0 50Δ AC static state current

#### **Output Specs**

Output voltage range 4-15Vdc 30W Output power Bulk charge current rating 2A@12Vdc Bulk charge voltage rating 14.7Vdc Float charge voltage rating 13.2Vdc Light switching current 0.40A

#### **General Specs**

Efficiency 78% Over load protection <3A Short circuit protection Yes Reversed polarity connectors protection Yes Operating temperature 0°C-40°C Storage temperature -30°C-85°C Net weight 600g 154\*72\*47mm Dimensions Enclosure Plastic Case Application Indoor Charger type Wall mounting

#### Safety Specs

Withstand voltage (Hi-Pot) 3000Vac ≤ 10mA (60s) >100MΩ @500Vdc Insulation resistance UL1012/CSA/CE Class B Safety standard Compliance FCC,ETL,DOE,CE

#### Indicator

Green - Float or empty load Yellow Flash - Short or Reversed Polarity

Yellow - Bulk charge Red - Power on

## MODELS - INPUT PLUGS & CONNECTIONS

MODELS IN STILLOGG & CONNECTIONS			
Part Number	Input Plug	Output Connection	
PSC122000ACX-US	NEMA-A	Alligator Clips	
PSC122000ACX-EU	CEE-C	Alligator Clips	
PSC122000ACX-UK	BS-G	Alligator Clips	
PSC122000PS-US	NEMA-A	Alligator/Ring Clips	
PSC122000PS-EU	CEE-C	Alligator/Ring Clips	
PSC122000PS-UK	BS-G	Alligator/Ring Clips	

#### **FURTHER INFORMATION**

Please refer to our website www.power-sonic.com for a complete range of useful downloads, such as product catalogs, safety data sheets, ISO